

**THAT WHICH IS CLAIMED IS:**

1. A trading card optical compact disc compatible with a disc reader which includes a centrally located spindle and a seating ring for supporting and rotating a compact disc positioned thereon, the trading card optical compact disc comprising;
- 5 at least a first plastic rectangular layer having a width of about 2.5 inches and a length of about 3.5 inches and having a pattern of digital data encoded thereon;
- a second metallic layer formed on at least portions of the first plastic layer;
- 10 a third protective layer formed on at least the second layer for protecting the metallic layer,
- an indicia bearing fourth layer formed on the third layer and having a generally planar upper surface for displaying indicia therefrom;
- an opening extending through the first, second, third, and fourth
- 15 layers in a medial portion thereof; and
- trading card interface seating means integrally formed in at least the first layer for seating the trading card onto a loading tray of a disc reader so as to interface with only portions of the seating ring and not other portions of the seating ring of the disc reader and to read digital data stored thereon from the trading card optical compact disc.
2. A trading card optical compact disc as defined in Claim 1, wherein said trading card seating means comprises at least said first plastic layer including a major elevational portion having a first predetermined height and a minor elevational portion having a second predetermined height, the
- 5 major elevational portion having the encoded digital data thereon and the minor elevational portion being devoid of the encoded digital data.
3. A trading card optical compact disc as defined in Claim 2, wherein the major elevational portion is formed in a medial portion of the

009200-00000

5

5

5.

6.

**7.**

9. A trading card optical compact disc as defined in Claim 8, wherein the first non-metallic zone includes a stacking ring surrounding the opening for stacking another optical compact disc thereon.

at least a first polycarbonate rectangular layer having a width of about 2.5 inches and a length of about 3.5 inches and having a pattern of digital data encoded thereon, said first plastic layer including a major elevational portion having a first predetermined height and a minor elevational portion having a second predetermined height so that the major elevational portion interfacingly seats the trading card onto a loading tray of a disc reader so as to interface with only portions of the seating ring and not other portions of the seating ring of the disc reader and to read digital data stored thereon from the trading card optical compact disc, the major elevational portion having the encoded digital data thereon and the minor elevational portion being devoid of the encoded digital data, the major elevational portion being formed in a medial portion of the trading card and having first and second pairs of spaced-apart outer side peripheries defining outer boundaries of the major elevational portion, each of the first pair of space-apart outer side peripheries arcuately extending between each of the second pair of space-apart outer side peripheries, and each of the second pair of space-apart outer

a second metallic layer formed on at least portions of the first polycarbonate layer;

an opening extending through the first, second, and third layers  
in a medial portion thereof.

12. A trading card optical compact disc as defined in Claim 11, wherein the encoded digital data of the major portions of said first layer is formed within a circular data zone and comprises less than the entire surface area of the major elevational portion of said first layer.

14. A trading card optical compact disc as defined in Claim 13, further comprising a first non-metallic zone surrounding and extending outwardly a predetermined distance from the medial opening and a second

non-metallic zone extending inwardly from the rectangular outer perimeter of the trading card optical compact disc a predetermined distance.

15. A trading card optical compact disc as defined in Claim 14, wherein the first non-metallic zone includes a stacking ring surrounding the opening for stacking another optical compact disc thereon.

16. A trading card optical compact disc comprising:

at least a first polycarbonate rectangular layer having a width of about 2.5 inches and a length of about 3.5 inches and having a pattern of digital data encoded thereon, said first plastic layer including a major elevational portion and a minor elevational portion, the major elevational portion having the encoded digital data thereon and the minor elevational portion being devoid of the encoded digital data, the major elevational portion being formed in a medial portion of the trading card and having first and second pairs of spaced-apart outer side peripheries defining outer boundaries of the major elevational portion, each of the first pair of space-apart outer side peripheries arcuately extending between each of the second pair of space-apart outer side peripheries, and each of the second pair of space-apart outer side peripheries extending generally linearly between each of the first pair of spaced-apart outer peripheries;

15 a second metallic layer formed on at least portions of the first polycarbonate layer;

at least a third layer formed on at least the second layer for protecting the metallic layer and for displaying indicia therefrom;

20 an opening extending through the first, second, and third layers in a medial portion thereof;

a first non-metallic zone surrounding and extending outwardly a predetermined distance from the medial opening; and

[illegible]

17. A trading card optical compact disc as defined in Claim 16, wherein each of the arcuately-extending first pair of spaced-apart outer side peripheries of the major elevational portion are centered about an axis extending through the medial opening and generally perpendicular to the linearly-extending second pair of space-apart outer side peripheries, and wherein a radius extending from a medial portion of said medial opening to each of the arcuately-extending first pair of spaced-apart outer side peripheries of the major elevational portion is less than 1.6 inches.
18. A trading card optical compact disc as defined in Claim 17, wherein the encoded digital data of the major portions of said first layer is formed within a circular data zone and comprises less than the entire surface area of the major elevational portion of said first layer.
19. A trading card optical compact disc as defined in Claim 18, wherein the circular data zone has a first inner circular periphery having a radius of at least 0.6 inches and a second outer circular periphery having a radius of less than 1.25 inches.
20. A trading card optical compact disc as defined in Claim 16, wherein the first non-metallic zone includes a stacking ring surrounding the opening for stacking another optical compact disc thereon.
21. A trading card optical compact disc having a width of about 2.5 inches and a length of about 3.5 inches, the trading card optical compact disc comprising:

5  
10  
15

plastic layer;

20

in a medial portion thereof;

25

rectangular outer perimeter of the trading card optical compact disc a predetermined distance.

5

claims  
25-31  
class  
264/  
1.33

5

the step of rotating the tra  
encoded data therefrom.

5

5



claims  
32-34  
class  
156/60

- positioning a compact disc having a pattern of digital data encoded thereon onto a medial portion of a surface of a trading card having a width of about 2.5 inches and a length of about 3.5 inches, the combination of the compact disc and the trading card having a major elevational portion and a minor elevational portion so that the major elevational portion interfacingly seats the combination onto a loading tray of a disc reader so as

10 to interface with only portions of the seating ring and not other portions of the  
seating ring of the disc reader and to read digital data stored thereon from the  
trading card optical compact disc, the major elevational portion having the  
encoded digital data thereon and the minor elevational portion being devoid  
of the encoded digital data, the major elevational portion having first and  
second pairs of spaced-apart outer side peripheries defining outer boundaries  
15 of the major elevational portion, each of the first pair of space-apart outer side  
peripheries arcuately extending between each of the second pair of space-  
apart outer side peripheries, and each of the second pair of space-apart outer  
side peripheries extending generally linearly between each of the first pair of  
spaced-apart outer peripheries.

33. A method as defined in Claim 32, wherein the major  
elevational portion is formed in a medial portion of the trading card and has  
first and second pairs of spaced-apart outer side peripheries defining outer  
boundaries of the major elevational portion, each of the first pair of space-  
5 apart outer side peripheries arcuately extending from each of the second pair  
of space-apart outer side peripheries, and each of the second pair of space-  
apart outer side peripheries extending generally linearly from each of the first  
pair of spaced-apart outer peripheries.

34. A method as defined in Claim 33, wherein the  
combination includes an opening formed in a medial portion thereof, wherein  
each of the arcuately-extending first pair of spaced-apart outer side  
peripheries of the major elevational portion are centered about an axis  
5 extending through the medial opening and generally perpendicular to the  
linearly-extending second pair of space-apart outer side peripheries, and  
wherein a radius extending from a medial portion of the medial opening to  
each of the arcuately-extending first pair of spaced-apart outer side  
peripheries of the major elevational portion is less than 1.6 inches.

00928280 002204